



ENCLOSURE

ENCL1



Features :



Removable Door



Lock with 2 Keys



PS-1224 Mount

ENCL1 is a robust enclosure designed to house a variety of RBH controllers.

It features convenient removable cover mounted on heavy duty hinges and allowing 170° swing and lock.

Installation is made convenient by a number of conduit access points on all sides of the enclosure.



Temper switch ready



Ventilation Slats



Knock outs for 3/4" conduit

ENCL1

SPECIFICATIONS

• ENCL1

Includes:

Lock with 2 keys



• ENCL1-PS

Includes:

Lock with 2 keys

PS-1224 Power Supply

In : 16.5 VAC 40 VA

Out : 12 VDC @ 2.5A



Works with :

NC-100, RC-2, IOC-16

UNC-500

IRC-2000

URC-2000 (up to 2)

ELV8 (up to 2)

Dimensions : Metal housing with 3 mounting holes

Width : 12" (30.5 cm)

Height : 14" (35.5 cm)

Depth : 3 1/4" (8 cm)

Conduit Access : 10

Top : 3 of 3/4" knockouts

Bottom : 3 of 3/4" knockouts

Left : 2 of 3/4" knockouts

Right : 2 of 3/4" knockouts

Temper switch : Optional

Weight : 7.5 lbs (3.4 Kg)



**Specifications are subject to change without notice.



© RBH Access Technologies, Inc. 2010

Head Office

RBH Access Technologies, Inc.

2 Automatic Drive, Suite 108

Brampton, ON Canada

L6S 6K8

Tel. +1-905-790-1515

Fax. +1-905-790-3680

info@rbh-access.com

www.rbh-access.com

Europe

ARAS & RBH Security Group Ltd.

F3 Enterprise Way, Vale Business Park

Evesham, Worcestershire UK

WR11 6GS

Tel. +44(0)-1386-425810

Fax. +44(0)-1386-425811

info@aras-rbh.com

www.aras-rbh.com

USA

RBH USA, Inc.

60 Whitney Rd., Suite 14

Mahwah, NJ 07430

Tel. 201-663-9070

Toll free : 877-251-3550

Fax. 201-891-3420

info@rbh-access.com

www.rbh-access.com