

## IP Based Standalone RFID Access Control Terminal + Reader



### SCR 100

(No LCD & Keypad)

153 mm \* 95.5 mm \* 35.5 mm

SCR100 & SC405 are professional access control terminals, specially designed for the international high terminal access control market to substitute multi door controller concept.

Our SC Series products are the next evolution in access control hardware solutions. A true IP solution that meets the demands of open architecture, IP-centric environments. They provide fully distributed intelligence and decision making right to the door, leveraging the IT infrastructure to the maximum extent possible.

#### Features

- \* IP Based Standalone networkable machine
- \* Universal standard Weigand INPUT/OUPUT options
- \* Inbuilt relay to communicate with Locks, Alarms & Door Sensors
- \* Built in optional embeded web server to access data



### SC 405

(With LCD & Keypad)

129 mm \* 100 mm \* 40 mm

## Technical Specification

Users: 30,000 Cards

Transaction: 50,000 Logs

CPU: 32bit Microprocessor

Identification speed: <=1 Sec

Read range: 8 - 10 cms

Communication: RS232, RS485, TCP/IP

Wiegand I/O: 26 bit

USB 2.0 Port

Operation temperature: 0°C - 45°C

Operation Humidity: 20-80%

Power: 12V DC, 400mA

Access control: 50 time zones, 5 group, 10 time combination

Optional Functions: Web server, Work code, Antipass, ID/Mifare/HID card reader

